



1500VDC 3 INPUT FUSED TRUNK BUSS

ABOUT

Olson Motor & Control 1500VDC 3 Input Fused, Trunk Buss Combiner Box .
Designed for up to (3) positive fused input trunk cables, 1XL blade size, 50 - 200A.

SPECIFICATIONS

VOLTAGE	1500VDC
AMPERAGE	400 AMP
POSITIVE FUSE AMPERAGE RATING RANGE	50, 63, 80, 100, 125, 160 200A
DISCONNECT KA RATING	10 KAIC
INPUTS	3
POSITIVE TRUNK INPUT CONNECTION	M10 SINGLE HOLE LUGS, CU ONLY
NEGATIVE TRUNK OUTPUT CONNECTION	M10 SINGLE HOLE LUGS, CU ONLY
POSITIVE & NEGATIVE TO INVERTER CABLE RANGES	M10 - M12, SINGLE HOLE LUG, 4/0 - 750KCMIL
STANDARD/COMPLIANCE	UL1741
STANDARD ENCLOSURE	NEMA4 PAINTED STEEL
STANDARD FEATURES	LEXAN SAFETY SHIELD, SURGE PROTECTION, OMC MOUNTING BRACKETS, NEMA4X BREATHER DRAIN



OPTIONS

NEMA4 X FIBERGLASS ENCLOSURES	2-HOLE OUTPUT LUG PROVISIONS
PRE-PUNCHED CONDUIT ENTRY	FACTORY INSTALLED CABLE GLANDS

CONTACT INFO

1908 AEROTECH DR. SUITE 150
COLORADO SPRINGS, CO

908-231-1500

SALES@OLSONMC.COM