



# 1500VDC LOAD BREAK DISCONNECT

## ABOUT

Olson Motor & Control 1500VDC Load Break Disconnect Enclosure

## SPECIFICATIONS

VOLTAGE	1500VDC
AMPERAGE	400 AMP
DISCONNECT KA RATING	10 KAIC
INPUT WIRE RANGE	4/0 - 750 KCMIL CU OR AL
OUTPUT WIRE RANGE	4/0 - 750 KCMIL CU OR AL
STANDARD/COMPLIANCE	UL1741
STANDARD ENCLOSURE	NEMA4 PAINTED STEEL
STANDARD FEATURES	LEXAN SAFETY SHIELD, SURGE PROTECTION, OMC MOUNTING BRACKETS, NEMA4X BREATHER DRAIN



## OPTIONS


NEMA4 X FIBERGLASS ENCLOSURES	2-HOLE OUTPUT LUG PROVISIONS
PRE-PUNCHED CONDUIT ENTRY	FACTORY INSTALLED CABLE GLANDS

## COMING SOON!

500A LOAD BREAK DISCONNECT MODEL, UL1741 APPROVAL PENDING

## CONTACT INFO

1908 AEROTECH DR. SUITE 150  
COLORADO SPRINGS, CO

 908-231-1500

 SALES@OLSONMC.COM